

高强度水气管 A4-010



应用:

■ 一种优质多功能工业管，广泛应用于工厂、建筑、农业、采石场、矿井、铁路、石油和天然气工业、以及造船业。所有尺寸的最大工作压力都在500psi (3.4Mpa)。软管不导电，在1000伏特直流电条件下，其每英寸的最小电阻大于1兆欧姆

技术参数:

- 内层: 丁腈橡胶内层, RMA抗油A等级 (高耐油性)
- 增强层: Flexten合成纤维缠绕, 2"的是合成纤维编织
- 外层: 黄色的Carbryn合成橡胶, RMA抗油A等级 (高耐油性) 通过MSHA认证
- 工作温度: -20° F到210° F (-29° C到99° C)

Applications:

■ A premium-quality, multi purpose industrial hose with a wide range of applications in factories, construction, agriculture, quarries, mines, railroads, the oil and gas industry, and shipbuilding. All sizes are rated at 500 psi (3.4Mpa) maximum working pressure. Non-conductive, minimum electrical resistance greater than one megohm per inch of hose length at 1000 Volts DC

Technical description:

- Tube: Nitrile synthetic rubber, RMA Class A (High Oil Resistance)
- Reinforcement: Spiral Flexten yarn, 2" is braided synthetic yarn
- Cover: Yellow Carboxylated synthetic rubber, RMA Class A (High Oil Resistance) MSHA approved
- Temperature: -29°C to 99°C

高强度水气管 GORILLA

产品编码 No.	内径		外径 mm	工作压力 bar	重量 kg/m	包装长度 m
	in	mm				
A4-010-0190	3/16"	4.8	11.9	34.5	0.12	152.4
A4-010-0250	1/4"	6.4	15.5	34.5	0.25	152.4
A4-010-0310	5/16"	7.9	17.5	34.5	0.3	152.4
A4-010-0380	3/8"	9.5	18.6	34.5	0.33	152.4
A4-010-0500	1/2"	12.7	22.6	34.5	0.42	152.4
A4-010-0630	5/8"	15.9	26.9	34.5	0.52	152.4
A4-010-0750	3/4"	19.1	30.2	34.5	0.61	152.4
A4-010-1000	1"	25.4	37.8	34.5	0.86	152.4
A4-010-1250	1-1/4"	31.8	45.6	34.5	1.18	152.4
A4-010-1500	1-1/2"	38.1	51.8	34.5	1.27	152.4
A4-010-2000	2"	50.8	66.6	34.5	1.82	152.4

blueFuture
您身边的工业专家