

液压吸排磨损波纹管 A1-152



应用:

- 波纹状硬壁排吸管，特别适合输送大量磨损性物料，如沙石、木屑、水泥等，特别适用于液压机械设备

优点:

- 优异的耐磨损性能
- 安装方便
- 具有良好的弯曲半径
- 良好突然冲击下的减压性能
- 可有效减少压力损耗
- 良好的减震和降噪性能
- 可适应各类复杂的气候条件

技术参数:

- 内胶: 黑色, 光滑, 耐磨损, NR合成橡胶
- 增强层: 高强度合成线绳, 内置螺旋钢丝加固
- 外胶: 黑色波纹管, EPDM合成橡胶, 抗老化, 耐臭氧, 表面布纹
- 温度范围: -30℃至+70℃
- 导电性能: 内胶导电, $R < 2.16\Omega/m$ (装配接头时, 要注意跟螺旋钢丝连接在一起)

Applications:

- Hydraulic suction or discharge of abrasive materials

Advantages:

- Excellent resistance to abrasion
- Can be supplied cut to length for on-site coupling
- Quick and easy installation
- Light weight and low bending radius
- Low installation cost
- Electrical conductivity ensured by the helix
- Suppression of pressure surges
- Reduction in pressure head loss
- Damping of vibrations and noise
- Excellent weather resistance

Technical Description:

- Inner tube: wear resistant NR, black, smooth
- Reinforcement: synthetic textile with embedded steel helix
- Cover: weather resistant EPDM, black, corrugated, fabric impression
- Temperature range: -30 °C to + 70 °C
- Electrical properties: conductive tube and cover (helix must be connected with couplings)

液压吸排磨损波纹管

PERFORMER GL AD10H

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A1-152-1000	1	25	53.0	10	30	125	1.97	20
A1-152-1250	1-1/4	32	60.0	10	30	160	2.33	20
A1-152-1580	1-9/16	40	73.0	10	30	200	3.37	20
A1-152-2000	2	50	83.0	10	30	250	4.04	20
A1-152-2580	2-9/16	65	98.0	10	30	325	4.99	20
A1-152-3190	3-3/16	80	113.0	10	30	400	5.90	20
A1-152-4000	4	100	133.0	10	30	500	7.12	20
A1-152-5000	5	125	158.0	10	30	750	8.72	20
A1-152-6000	6	150	183.0	10	30	1050	10.20	20
A1-152-8000	8	200	234.5	10	30	1600	14.31	12
A1-152-10000	10	250	285.5	10	30	2000	18.90	12
A1-152-12000	12	300	340.5	10	30	2500	25.30	12
A1-152-14000	14	350	391.0	10	30	3100	31.47	12
A1-152-16000	16	400	441.0	10	30	4000	36.39	12

blueFuture

您身边的工业专家